

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана (7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04

Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15

Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Единый адрес: oci@nt-rt.ru Веб-сайт: www.oi.nt-rt.ru

TOC анализатор 1030S OI Analytical

Need to analyze total organic carbon (TOC) or total carbon (TC) in solid materials? That's exactly why we built the 1030S Solids Analysis Module. This sample preparation module is the perfect complement to the Aurora 1030W or 1030C TOC analyzers.

Smartly designed, the compact instrument saves bench space while it is hard at work combusting solid materials, soils, sludge, slurries, and powders for TC and TOC analysis.



Principle of Operation

Total organic carbon (TOC) is determined by manually transferring and weighing a solid sample into a quartz sample cup. The total inorganic carbon (TIC) content is removed from the sample by adding acid and heating to drive off CO₂ released from inorganic carbon compounds. In the case of total carbon (TC) analysis, the pre-acidification step to remove TIC content is not required.

The sample cup with the TIC-free sample is placed on the lift mechanism and raised into the combustion tube of the 1030S. The sample is heated to 500° - 900 °C inside the furnace. Organic matter in the sample is oxidized and converted to CO₂ which is collected in a one liter capacity gas sampling bag. When the combustion cycle is complete an aliquot of the CO₂ sample gas is transferred to the NDIR detector in the Aurora 1030 oci analyzer for measurement of the mass of carbon in the sample.

1030S Features:

Combusts solid materials soils, sludge, slurries, and powders for TC and TOC analysis

Interfaces with Aurora 1030 TOC analyzer allowing analysis of both solid and liquid samples using a single instrument

Gas sampling device (patent pending) collects carbon dioxide (CO₂) from sample combustion for quantitation and analysis of intra-sample replicates

Compact vertical design saves laboratory bench space

Operating Principle

Catalytic combustion in oxygen

Sample Combustion Temperature

500 °C – 900 °C (in 1 °C increments)

Operating Modes	TC, TOC (requires pre-acidification and TIC bakeout)
Detection/Measurement	Non-dispersive infrared detector in Aurora 1030 TOC Analyzer
Measurement Range	0.05–mg C to 50-mg C (*determined using graphite)
Measurement Accuracy	+ 10%
Sample Size (Mass)	50 µg to 2 grams (maximum) dependent upon carbon content (10 to 100 mg typical)
Sample Cup Volume	Large: 2.5 mL Small: 1.0mL
Gas Sample Bag Volume	1 liter
Gas Replicates from Sample Bag	5 maximum
Gas Sample Aliquot Volume Range (1030S + 1030W)	1 to 9 mL
Gas Sample Aliquot Volume Range (1030S + 1030C)	0.25 to 2 mL
Intra-sample Precision (Replicates from Gas Sample Bag)	< 3% RSD
Inter-sample Precision	< 10% RSD
Calibration	Single- or multi-point calibration (up to 12 points)
Sample Combustion/Analysis Cycle Time	14 minutes (typical)
Sample Preparation	TIC removal via preliminary manual, offline sample acidification step and heating @ 75-500 °C (250 °C optimal)
Standard Method Compliance	SW 846 Method 9060A, ISO 10694:1995, ASTM E1915
Certifications – Safety	Low Voltage Directive (2006/95/EC) IEC–61010-1:2001

Certifications – EMI

Directive 89/336/EEC:1989, EN61326-1:2006
CISPR 11:2003 Conducted Emissions
CISPR 11:2003 Radiated Emissions

Gas Requirements

Reaction/Carrier Gas: Oxygen > 99.8% purity, 20 psi (138 kPa)

Power Requirements

115 (±10%) VAC, 50/60 Hz, 500 VA
230 (±10%) VAC, 50/60 Hz, 500 VA

Power Consumption

480 VA under maximum load conditions

Dimensions

24 in. H x 8.125 in. W x 17.25 in D
(61 cm x 20.6 cm x 43.8 cm)

Weight

24 lbs (10.8 kg)

Patents

U.S. Patent No. 8,191,437

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана (7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04

Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижегород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15

Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Единый адрес: oci@nt-rt.ru **Веб-сайт:** www.oi.nt-rt.ru